



ADVANCED PHOTONICS
TACTICAL THERMAL
WEAPON SIGHTS


TI-GEAR-S6100

The TI-GEAR-S6100 is the professional-grade thermal weapon sight for aiming and engagement on a wide variety of firearms at medium-to and long-range distances. Ideal for both small, large-size caliber rifles, machine guns, whether single or repetitive shooting. It is also a great tool for reconnaissance and tactical surveillance.

The latest generation silent and Auto-NUC sensor is at the base of the TI-GEAR-S6100. GSCI proprietary hardware and software solutions are built around the sensor and offer exceptional image quality along with unique tools for added tactical advantage and user safety.

The TI-GEAR-S6100 is fully dust- and waterproof, meets and exceeds modern MIL standards. The TI-GEAR-S6100 is designed for both professional users and also firearms enthusiasts. It is a robust, reliable tool for long-term, intensive use in any environment, in any lighting or weather conditions.

ADVANTAGES OF TI-GEAR-S6100



Designed, Developed, Manufactured by GENERAL STARLIGHT COMPANY INC.
120 WHITMORE ROAD, UNIT 20, WOODBRIDGE, ONTARIO, L4L6A5, CANADA
WWW.GSCI1.COM | GSCI@GSCI1.COM | +1.905.850.0990

DISCLAIMER. Technical description, certain optical-electronic-mechanical features of the product shown herein and/or some of its parts/components may not precisely represent the actual device and are subject to change without prior notice by the sole discretion of General Starlight Company, Inc. Mass of the product represents measurable weight of all components this product consists of, such as optics, mechanics and electronics. Weight of Image Intensifier tubes may vary depending on the type and make of Image Intensifier tube being used and therefore is listed separately. Dimensions of the product represents measurable size of the body, including all optical components attached and in fully folded position. Dimensions of additions such as mounting brackets, eyecups, objective lens covers, and/or battery extensions may vary and therefore are not listed herein. Copyright © 1992-2020 General Starlight Co., Inc. Canada. All rights reserved.



ADVANCED PHOTONICS
TACTICAL THERMAL
WEAPON SIGHTS

TI-GEAR-S6100

Every TI-GEAR-S6100 Sight can be used in 3 main configurations



Hand-Held

Removing Weapon Mount is not necessary



Standalone Sight



Clip-On (In-Line) Sight

Clip-On Adapter Required



Designed, Developed, Manufactured by GENERAL STARLIGHT COMPANY INC.
120 WHITMORE ROAD, UNIT 20, WOODBRIDGE, ONTARIO, L4L6A5, CANADA
WWW.GSCI1.COM | GSCI@GSCI1.COM | +1.905.850.0990

DISCLAIMER. Technical description, certain optical-electronic-mechanical features of the product shown herein and/or some of its parts/components may not precisely represent the actual device and are subject to change without prior notice by the sole discretion of General Starlight Company, Inc. Mass of the product represents measurable weight of all components this product consists of, such as optics, mechanics and electronics. Weight of Image Intensifier tubes may vary depending on the type and make of Image Intensifier tube being used and therefore is listed separately. Dimensions of the product represents measurable size of the body, including all optical components attached and in fully folded position. Dimensions of additions such as mounting brackets, eyecups, objective lens covers, and/or battery extensions may vary and therefore are not listed herein. Copyright © 1992-2020 General Starlight Co., Inc. Canada. All rights reserved.



ADVANCED PHOTONICS
TACTICAL THERMAL
WEAPON SIGHTS
TI-GEAR-S6100

TI-GEAR-S6100 TECHNICAL DATA

Optical Magnification	4X
Objective Lens System	100mm, f/1.3
Field of View	6.2°x4.7°
Focusing Range	4m .. Infinity
Diopter Adjustment Range	-6 .. +4
Eyerelief	Min. 50mm
FPA Type	Uncooled, a-Si, Shutterless, Silent, Auto-NUC (Uninterrupted Operation)
FPA Resolution and Pitch	640x480, 17µm
FPA Sensitivity (NETD)	<50mK
FPA Refresh Rate	50Hz
Digital Zoom	1X, 2X, 4X
Internal Display	Full Size: 0.6-Inch Diagonal, AMOLED, Colour, 800x600
Imaging Modes	Monochrome (White-Hot / Black-Hot) and Multiple Colour Palettes
Shot-Initiated FOV Feature (SIF)	Built-In Adjustable Shock Sensor
Digital Passive Stadiametric Rangefinder (SRF)	Yes
Digital Detail Enhancement Feature (DDE)	Yes: 7 Levels
Digital Edge Detection Feature (DED)	Yes
Wide Dynamic Range Feature (WDR)	Yes
Stow Safety Feature (SSF)	Yes
Integrated 9-Axis Absolute Orientation HUD (Heads-Up Display)	Yes: 3-Axis Sensors - Magnetometer, Accelerometer and Gyroscope
Integrated Compass	Yes
Pitch / Roll / Azimuth Indications	Yes
Real-Time Date-Time Stamp	Yes: Simplified, Extended, DTG Formats
Digital Video Recorder with Real-Time Stamp	Yes. Comes with removable 32GB microSD card
Electronic Reticles	8+8 Patterns, Easy Zeroing / Calibration
Detection Capability: Man (1.7x0.5m) / NATO Target (2.3x2.3m)	3330m / 4500m
Hand-Held Configuration	Yes
Conversion to Clip-On (In-Line) Sight	Yes
Tripod-Mountable Configuration	Yes
User Profiles (Configurable)	Yes: 8
Automatic/Manual Pixel Masking	Yes
Reset to Factory Defaults	Yes
External Video Feed Protection	Yes
Automatic Power Down Control	User-Configurable: 10 .. 60 minutes of inactivity
Accepted Batteries	2 (two) CR123 of Any Type: Lithium / Rechargeable
Universal Port	Video-Out, Remote Control and External Power (4VDC .. 15VDC)
Battery Life on 2x CR123	Up to 7 Hours
MIL-STD-810G Compliant	Yes
Environmental Protection	Min. IP67, Nitrogen-Purged Housing
Dimensions	230 x 85 x 85mm
Weight	750 grams
Operating Temperature	-40°C .. +50°C
Warranty	7 Years, Limited
Export	Available Worldwide (Canadian Export Permit Required. GSCI provides assistance in obtaining the Permit)

DISCLAIMER: Technical description, certain optical-electronic-mechanical features of the product shown herein and/or some of its parts/components may not precisely represent the actual device and are subject to change without prior notice by the sole discretion of General Starlight Company, Inc. Mass of the product represents measurable weight of all components this product consists of, such as optics, mechanics and electronics. Weight of image intensifier tubes may vary depending on the type and make of image intensifier tube being used and therefore is listed separately. Dimensions of the product represents measurable size of the body, including all optical components attached and in fully stowed position. Dimensions of additions such as mounting brackets, eyepieces, objective lens covers, and/or battery extensions may vary and therefore are not listed herein. Copyright © 1992-2020 General Starlight Co., Inc. Canada. All rights reserved.



ADVANCED PHOTONICS
TACTICAL THERMAL
WEAPON SIGHTS

TI-GEAR-S6100

STANDARD EQUIPMENT: WHAT'S IN THE BOX



TI-GEAR-S6100

Long-Eyerelief Eyecup, Lens Cover and Low Profile Weapon Mount Attached



Video-Out Cable



USB Power Cable



Soft Pouch



32GB microSD Card and SD Adapter



Demist Shield



Hard Case



User's Manual



Quick Reference Card



Warranty Form

OPTIONAL EQUIPMENT



MAK Rifle Mount: Available in Picatinny and Blaser variants (comes with a mounting adapter)



External Video Recorder with SD Card



Clip-On Adapter



Remote Control



Portable Head-Mounted Display HMD-800 (streams thermal video directly from the device)



Recoil Mitigation System RMS-50