DBAL-RL

DUAL BEAM AIMING LASERS SERIES

RIFLE LIGHT

THE STEINER EOPTICS PISTOL LIGHT LASERS SERIES ENABLES OPERATORS TO ENGAGE TARGETS ON A BATTLEFIELD OR DURING CLOSE-QUARTER COMBAT IN LOW-LIGHT AND NO-LIGHT CONDITIONS.

····· OVERALL FEATURES ······

- Program single tap, double tap, and press and hold functions and control the dimming level of each.
- Red or Green visible aiming laser, IR laser, IR illuminator & white light
- Co-aligned visible & IR aiming Lasers
- Fully adjustable windage and elevation
- Integrated adjustable Picatinny mount
- Powered by two CR123A Batteries
- Quick-release battery latches



Available in **Green** (79055) and **Red** (79045) Lasers





Push Button switches and dimming levels can be programmed.



Fully adjustable mounting bracket easily attaches to standard pistol rails or M1913 picatinny rails.



Bright white light and IR Illuminator sits below the laser pointers. Recoil resistant design ensures reliable performance.





..... DBAL-RL | RIFLE LIGHT AIMIN'G LASER SERIES



	SPECIF	ICATIONS '	
Dual Beam Aiming Lasers Series			
		79055	79045
LASER TYPE	Visible Laser	Green Class IIIa	Red Class IIIb
	IR Laser Pointer	Class I	Class I
	IR LED Illuminator	Eye-safe	Eye-safe
POWER	Visible Laser	<5 mW	<5 mW
	IR Laser Pointer	<0.7 mw	<0.7 mw
	IR LED Illuminator	<600 mW	<600 mW
	White Light	500 Lumens	500 Lumens
WAVELENGTH	Visible Red Laser	r	640 mW +/-2%
	Visible Green Laser	525 mW +/-3%	525 mW +/-3%
	IR Laser Pointer	840 +/-3%	840 +/-3%
	IR LED Illuminator	840 +/-3%	840 +/-3%
BEAM DIVERGENCE	Visible Laser	<0.8 mRad	<0.8 mRad
	IR Laser Pointer	<0.8 mRad	<0.8 mRad
	IR LED Illuminator	18°	18°
	White Light	18°	18°
RANGE/VISIBILITY (NIGHT/DAY)* Range may vary depending on light conditions	Visible Red Laser	-	750m/15m
	Visible Green Laser	750m/15m	+
	IR Laser Pointer	750m/15m	750m/15m
	IR LED Illuminator	>250 m	>250 m
R a	White Light	100 m	100 m
	Temperature	-20°C to +65° C	-40°C to +65° C
	Battery	CR123A (2)	CR123A (2)
	Battery Life (mode dependent)	>1.75 Hours	>1.75 Hours
	Material	Aircraft Aluminum	Aircraft Aluminum
	Color	Black	Black
	Weight (with battery) (oz.)	5.4	5.4
	Dimensions (in.) (LxWxH)	3.5 x 1.3 x 1.4	3.5 x 1.3 x 1.4
	Waterproof	Submersible to 5 m	Submersible to 5 m
	Mount	M1913 Rails	M1913 Rails
	Windage & Elevation Adjustment	Yes	Yes
	Activation Switch	Integrated Push Button(s) and Remote Cable	Integrated Push Button(s) and Remote Cable
	Programmable & Dimmable		
	Remote Cable Pressure Pad	Yes	Yes
	Warranty	2-Year	2-Year
			-



Steiner

3475 Newmark Drive, Miamisburg, OH 45342, USA PH: +1.937.426.2341, FAX: +1.937.426.4820 www.steiner-defense.com